

MP W6700SP

FULL SPECIFICATIONS

GENERAL

Configuration Console

Electro-photographic printing Copying/printing process Paper source: standard 2 Roll paper feeder 600 x 600 dpi

Grayscale printing 2 levels

Zoom 25% to 400% by 0.1% increments

Cutting method Preset size cut Synchronised cut

Variable cut

Hard Disk Drive 320 GB (shared with copier/printer/scanner) Power source 120 - 200 V, 20 A (max.), 60 Hz Dimensions (W x D x H)

1,250 x 755 x 1,215 mm 49.2 x 29.7 x 47.8"

230 kg Weight

507 lbs

COPIER

First copy time from standby

D-size: 19 seconds

mode

D-size: 6.7 ppm Copying speed

Copy modes Text, Text/Photo, Photo, Drawing, Generation Text, Generation Photo, Pasted Original, Background Line, Highlighter

Copier features Auto Paper Selection (APS), Auto Reduce/Enlargement, User Auto Reduce/Enlargement, Preset Reduce/Enlargement, Zoom, Size Magnification, Directional Size Magnification (percentage and mm/inch), Fine Magnification, Image Overlay, Format Overlay,

Negative/Positive, Mirroring, Double Copy, Repeat Copy, Image Shift - Front/Rear/Left/Right (0 to +/- 200 mm by 1 steps), Preset

Stamps, User Preset Stamps, Date Stamp, Page Stamp

PRINTER

Embedded Controller board 1.06 GHz CPU 6.7 ppm D-size LEF Print speed

3.3 ppm E-size SEF Up to 600 dp Print resolution Print drivers

Adobe Postscript HDI

Supported file formats HP-GL, HP-GL2, HP-RTL, TIFF, CALS, JPEG, PostScript, PDF, Microsoft Office, DWG/DWF

European 136 fonts (PS3) Fonts Network interface: standard 100 base-TX/10 base-T Ethernet Network interface: optional Wireless LAN IEEE 802.11a/g/n

TCP/IP (IPv4, IPv6) Network protocol: standard

Supported OS Windows® XP/Vista/7/8/8.1/2003 Server/2008 Server/2008R2 Server/2012 Server/2012R2 Server

Mac® OS (10.7 or later)

Printer features Sample Print, Auto Paper Select, Pen Setting, Media Selection, Stamp Setting, Roll Select, Language Setting, Set-up Launcher,

Online Help Menu, Multiple Print Sets, Combine Images, Locked Print Document Server, Remote Print via Internet, Magnification Mirror Setting, Border Setting, Set X and Y Axis, Transparency Mode, Delete After Printing, Engine Status Monitor, Encryption, PDF

Batch Print

English, Brazilian Portuguese, Danish, Dutch, Finnish, French, German, Italian, Japanese, Korean, Norwegian, Polish, Romanian, Supported languages

Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish

SCANNER

Color scan Standard Scan to multimedia Standard

Print from USB/SD (JPEG/TIFF/PDF) Media to print Scan speed: colour 26.7 mm/s or 1.05 ips (600 dpi) Scan speed: B/W 80 mm/s or 3.15 ips (600 dpi) 600 - 600 dpi

Scan resolution TWAIN: up to 1,200 dpi Scan modes: colour Text/Photo, Photo

Scan modes: B/W Text, Text/Photo, Text/Line Art (default), Photo, Drawing, Text/Drawing, Grayscale

Scan detection Auto Detect

Preset Paper Size Custom Size

RGB support Standard Network: TCP/IP Sal Dr Occ

Scan to email: SMTPPOP before SMTP Scan to folder: SMBFTPNCP imagine. change glevels of lighter to darker

www.ricoh-europe.com

Erase Border Positive/Negative Mirror Image

Document Server Full view: 18 x 24" Preview

Section preview: 36 x 48' Multi page TIFF, Single page TIFF, Multi page PDF, Single page PDF, Single page JPEG, High Compression PDF, PDF/A File formats

PAPER HANDLING

Original paper weight 14 - 28 lbs

Output paper weight 52.3 - 110 g/m² (Paper Roll)

Maximum thickness 1 mm, 0.04' ISO9001 certified ISO14001 certified. ISO27001 certified

names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

All brand and/or product